





TIOSP AND TIOSSB WEIGHING INDICATORS

CUTTING-EDGE TECHNOLOGY



TIO3P AND TIO3SB INDICATORS

The T103P and T103SB indicators are ideal for general weighing and simple counting applications. Ready for use in production, packaging, warehouse, inventory and shipping / receiving areas. Perfect for bench and floor scale applications. The T103P features an ABS housing and the T103SB features a NEMA 4X / IP65 water resistant stainless steel housing. Each indicator is equipped with a large backlit LCD display, raised tactile buttons, built-in rechargeable battery and simple operation. You can't go wrong with either indicator for your weighing applications that require a rugged and versatile indicator with an affordable price point.

T103P Features

- Durable, high-impact ABS housing
- Swivel bracket for desk or wall mounting
- 6-digit, 7-segment LCD display with 1" digit height
- High contrast white LED backlight
- Power to drive up to four 350Ω load cells
- · Parts counting function
- Bi-directional RS-232C serial data port for printer or PC connection
- Simple parameter setup and intuitive menu structure
- AC adapter and built-in rechargeable lead acid battery
- · Screw terminal load cell wiring

T103SB Features

- Large 1" LCD segments
- · Configurable white LED backlit display
- Stainless steel NEMA 4X / IP65 enclosure
- Wear resistant display panel overlay
- Powers up to (4) 350Ω cells
- Internal 100-240 VAC power supply
- Sealed lead-acid battery
- 58-hour typical single cell battery operation
- · Screw terminals for load cell wiring
- (1) duplex RS232 port
- Parts counting mode

NTEP Certificate of Conformance: 08-084A1

Canadian Approval: AM-6116C
Capacity Range: 5 to 20,000 lb or kg

Displayed Resolution: 1:20,000 max /1:6,000 NTEP

Weighing Units: lb, kg, g, oz

Overall Dimensions (W x D x H): 8.2 x 2.8 x 6.5 in. / 210 x 71 x 168 mm

Operating Temperature Range: 14 F° to 104 F° / -10 C to 40 C **Power:** 9 VDC, AC adapter or internal rechargeable battery

Battery: Sealed lead-acid battery (100 hour typical operation with full charge)







B-TEK Distributor